



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	308G-3
Cone Kit:	Kit not available.
Defective driver should be replaced.	
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	5
Sweep Frequency Hz:	30-1200
D.C. Resistance Ohms:	4.6 min/5.0 max
Gap Gauge:	N/A
Notes:	
If Not Serviceable, Replace With:	308G-1 or 508G
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different.
Replace both units in a stereo pair.	
HIGH FREQUENCY DRIVER:	012
Diaphragm Kit:	Kit not available.
Defective driver should be replaced.	
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	4
Sweep Frequency Hz:	1000-2000

HIGH FREQUENCY DRIVER (Cont'd)

D.C. Resistance Ohms:	3.6 min/4.4 max
Gap Gauge:	N/A
Notes:	Test With Network
If Not Serviceable, Replace With:	Currently Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A

SYSTEM SPECIFICATIONS:

Nom. Impedance:	8 Ohm
Rec. Amp Power Range:	10-100 Watts Per Channel
Crossover Frequency:	2500 Hz
Sensitivity:	90dB (1 Watt @ 1 Meter)
Enclosure Dim:	22" x 13-1/4" x 9-1/4" D 559mm x 337mm x 235mm
Shipping Weight:	70 lbs./pair - 32 kg./pair
Additional Parts Currently Available*:	
Grill:	GJ220A
Binding Posts: Red:	63635
Black:	63636

*Other parts may also be available. Check with JBL for details.