



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	310G-2
Cone Kit:	C4R310G-2
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	5
Sweep Frequency Hz:	30-1200
D.C. Resistance Ohms:	3.8 min/4.8 max
Gap Gauge:	.051"
Notes:	
If Not Serviceable, Replace With:	310G-3
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different.
	Replace both units in a stereo pair.
Additional Parts Currently Available*:	
Dome:	61521
Mounting Gasket:	60979
MID RANGE DRIVER:	305G-2
Cone Kit:	C4R305G-2
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	4
Sweep Frequency Hz:	75-3000
D.C. Resistance Ohms:	3.8 min/4.6 max
Gap Gauge:	.040"
Notes:	
If Not Serviceable, Replace With:	Currently Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A

MID RANGE DRIVER (Cont'd)

Additional Parts Currently Available*:

Dome:	54721
HIGH FREQUENCY DRIVER:	011
Diaphragm Kit:	Diaphragm Kit not available. Defective driver should be replaced.
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	3
Sweep Frequency Hz:	2000-12000
D.C. Resistance Ohms:	2.7 min/3.3 max
Gap Gauge:	N/A
Notes:	
If Not Serviceable, Replace With:	012
Visual Change:	Yes
Baffle Modification:	Yes
Exact Acoustic Replacement:	No. Slightly different.
	Replace both units in a stereo pair.

SYSTEM SPECIFICATIONS:

Nom. Impedance:	8 Ohm
Rec. Amp Power Range:	10-125 Watts Per Channel
Crossover Frequencies:	1000 Hz, 6000 Hz
Sensitivity:	89dB (1 Watt @ 1 Meter)
Enclosure Dim:	26" x 15-3/4" x 9-1/4" D 660mm x 400mm x 235mm
Shipping Weight:	42 lbs. - 19.1 kg.
Additional Parts Currently Available*:	
Grill:	G325
Binding Posts:	Red: 63635 Black: 63636

*Other parts may also be available. Check with JBL for details.