



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER: 123A-1
 Cone Kit: C8R2212
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 6
 Sweep Frequency Hz: 20-1200
 D.C. Resistance Ohms: 4.5 minimum
 5.5 maximum
 Gap Gauge: .044"
 Notes: Aquaplas
 If Not Serviceable, 2213H
 Replace With: (Reverse Polarity)
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No.
 Slightly different. Replace both units in a stereo pair.
 Additional Parts Currently Available*:
 Dome: 31385
 Trim Gasket: 32756

MID RANGE DRIVER: LE5-2
 Cone Kit: C8RLE52
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 4
 Sweep Frequency Hz: 75-3000
 D.C. Resistance Ohms: 5.5 minimum
 6.5 maximum
 Gap Gauge: .040"
 Notes: Dome Inverted
 If Not Serviceable,
 Replace With: LE5-10
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No.
 Slightly different. Replace both units in a stereo pair.

MID RANGE DRIVER (Cont'd)

Additional Parts Currently Available*:
 Dome: 54721
 Trim Gasket: 29931

HIGH FREQUENCY DRIVER: LE25
 Diaphragm Kit: D8RLE25
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 3
 Sweep Frequency Hz: 500-1200
 D.C. Resistance Ohms: 3.7 minimum
 4.2 maximum
 Gap Gauge: .029"
 Notes:
 If Not Serviceable,
 Replace With: 035TiA
 Visual Change: Yes
 Baffle Modification: Yes
 Exact Acoustic Replacement: No.
 Slightly different. Replace both units in a stereo pair.
 Additional Parts Currently Available*:
 Trim Ring: 50402
 Mounting Gasket: 50949-01
 Dome: 21606

SYSTEM SPECIFICATIONS:

Nominal Impedance: 8 Ohm
 Power Capacity: 50 Watts
 Continuous Program
 Crossover Frequencies: 1500 Hz, 6000 Hz
 Sensitivity: 78dB (1 Watt @ 15 Feet)
 Enclosure Dim: 14-1/4" x 23-1/2" x 13-5/8" D
 36.2cm x 59.7cm x 34.6cm
 Shipping Weight: 55 lbs. - 25 kg.
 Additional Parts Currently Available*:
 Grill: G100-Cloth
 Binding Posts: Red: 56131
 Black: 56130

*Other parts may also be available. Check with JBL for details.