



**SYSTEM COMPONENTS:**

- LOW FREQUENCY DRIVER:**
- 136A (L300)
  - 136H (L300A)
  - Cone Kit: C8R2235
  - Nom. Impedance: 8 Ohm
  - Dynamic Test Input V: 10
  - Sweep Frequency Hz: 20-1200
  - D.C. Resistance Ohms: 5.7 min/6.9 max
  - Gap Gauge: .057"
  - Notes: Mass Ring
  - If Not Serviceable, Replace With: 2235H
  - Visual Change: Yes
  - Baffle Modification: No
  - Exact Acoustic Replacement: No. Slightly different.
  - Replace both units in a stereo pair.
  - Additional Parts Currently Available\*:
    - Dome: 50201
    - Mounting Gasket: 34499
    - Trim Gasket: 52347

- MID RANGE DRIVER:**
- LE85
  - Diaphragm Kit: D16R2421
  - Nom. Impedance: 16 Ohm
  - Dynamic Test Input V: 3.5
  - Sweep Frequency Hz: 550-1200
  - D.C. Resistance Ohms: 5.9 min/7.0 max
  - Gap Gauge: .031"
  - Notes: H92 Horn/L92 Lens no longer available
  - If Not Serviceable, Replace With: 2425J
  - Visual Change: Yes
  - Baffle Modification: No
  - Exact Acoustic Replacement: No. Slightly different.
  - Replace both parts in a stereo pair.

- HIGH FREQUENCY DRIVER:**
- 077
  - Diaphragm Kit: D16R2405
  - Nom. Impedance: 16 Ohm
  - Dynamic Test Input V: 7
  - Sweep Frequency Hz: 1000-3000
  - D.C. Resistance Ohms: 5.7 min/6.7 max
  - Gap Gauge: .025"
  - Notes: Test With Network.
  - Do Not Crease Diaphragm.
  - If Not Serviceable, Replace With: 2405H
  - Visual Change: Yes
  - Baffle Modification: No
  - Exact Acoustic Replacement: Yes
  - Additional Parts Currently Available\*:
    - Mounting Gasket: 51795

**SYSTEM SPECIFICATIONS:**

- Nom. Impedance: 8 Ohm
- Max Rec. Amp Power: 300 Watts (L300)
- 400 Watts (L300A)
- Crossover Frequencies: 800 Hz, 8500 Hz
- Sensitivity: 93dB (1 Watt @ 1 Meter)
- Enclosure Dim: 31-5/8" x 23" x 22-1/2" D
- 803mm x 584mm x 572mm
- Shipping Weight: 145 lbs. - 66 kg. (L300)
- 152 lbs. - 69 kg. (L300A)
- Additional Parts Currently Available\*:
  - Binding Posts: Red: 10243 (L300) / 56131 (L300A)
  - Black: 10244 (L300) / 56130 (L300A)

\*Other parts may also be available. Check with JBL for details.