

Technical Manual

L44 Lancer



N/A

SYSTEM COMPONENTS:

FULL RANGE DRIVER: LE8T
Cone Kit: C8RLE8T
Nom. Impedance: 8 Ohm
Dynamic Test Input V: 4
Sweep Frequency Hz: 20-1200
D.C. Resistance Ohms: 5.1 minimum
5.9 maximum
Gap Gauge: .048"
Notes: Aquaplas On Cone.
Bond 2 foam pads to underside of dome.
If Not Serviceable,
Replace With: LE8T-H
Visual Change: Yes
Baffle Modification: No
Exact Acoustic Replacement: No.
Slightly different. Replace both units
in a stereo pair.
Additional Parts Currently Available*:
Dome: 21219
Mounting Gasket: 21769
Trim Gasket: 21812

PASSIVE RADIATOR: PR8
Cone Kit: CRPR8
Notes:
If Not Serviceable,
Replace With: No Replacement Available
Visual Change: N/A
Baffle Modification: N/A
Exact Acoustic
Replacement: N/A
Additional Parts Currently Available*:
Dome: 21219
Mounting Gasket: 21769
Trim Gasket: 21812

SYSTEM SPECIFICATIONS:

Nominal Impedance: 8 Ohm
Power Capacity: 20 Watts
Continuous Program
Crossover Frequency: N/A
Sensitivity: Not Published
Enclosure Dim: 12-3/4" x 23-1/2" x 11-3/4" D
324mm x 597mm x 298mm
Shipping Weight: Not Published
Additional Parts Currently Available*:

*Other parts may also be available. Check with JBL for details.