Technical Manual

L57 Carnival/ L59 Festival



N/A

SYSTEM COMPONENTS:

L57 FULL RANGE DRIVER:

Cone Kit:

Nom. Impedance:

Dynamic Test Input V:

Sweep Frequency Hz:

D.C. Resistance Ohms:

Gap Gauge:

Notes:

If Not Serviceable.

Replace With:

Visual Change:

Baffle Modification:

Exact Acoustic Replacement: No.

Slightly different. Replace both units

in a stereo pair.

Additional Parts Currently Available*:

L59 FULL RANGE DRIVER:

LE8T

Cone Kit:

C8RLE8T 8 Ohm

D280

C8R2110

8 Ohm

30-1200

044"

2118H

Yes

No

5.4 minimum

6.3 maximum

Aquaplas On Cone.

4

Nom. Impedance: Dynamic Test Input V:

4

Sweep Frequency Hz:

D.C. Resistance Ohms:

20-1200

5.1 minimum

5.9 maximum .048"

Gap Gauge: Notes:

Bond 2 foam pads to underside of dome.

Aquaplas On Cone.

LE8T-H

If Not Serviceable.

Replace With:

Visual Change: Baffle Modification:

No

Yes

L59 FULL RANGE DRIVER (Cont'd)

Exact Acoustic Replacement: No.

Slightly different. Replace both units

in a stereo pair.

Additional Parts Currently Available*:

Dome:

21219 21769

Mounting Gasket:

Trim Gasket:

21812

L56 AND L59

PASSIVE RADIATOR:

PR8

Cone Kit:

Notes:

If Not Serviceable,

Replace With:

Available

No Replacement

CRPR8

Visual Change:

N/A N/A

Baffle Modification:

Exact Acoustic Replacement: N/A

Additional Parts Currently Available*:

Dome:

21219

Mounting Gasket:

21769

Trim Gasket:

21812

SYSTEM SPECIFICATIONS:

NOT AVAILABLE

SYSTEM NOTES:

Systems are identical with the exception of

having different full range drivers.

^{*}Other parts may also be available. Check with JBL for details.