



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:

- Cone Kit: 129H
- Nom. Impedance: C8R129H
- Dynamic Test Input V: 8 Ohm
- Sweep Frequency Hz: 6
- D.C. Resistance Ohms: 20-1200
- Gap Gauge: 5.1 minimum
- Notes: 6.3 maximum
- Visual Change: .057"
- Baffle Modification: AquaPlas On Back
- Exact Acoustic Replacement: Of Cone

If Not Serviceable,

Replace With: 128H-1

- Visual Change: Yes
- Baffle Modification: No
- Exact Acoustic Replacement: Yes

Additional Parts Currently Available*:

- Dome: 31385
- Mounting Gasket: 20253
- Trim Gasket: 52806

MID RANGE DRIVER:

- Cone Kit: LE5-5
- Nom. Impedance: C8RLE59
- Dynamic Test Input V: 8 Ohm
- Sweep Frequency Hz: 4
- D.C. Resistance Ohms: 75-3000
- Gap Gauge: 5.6 minimum
- Notes: 6.6 maximum
- Visual Change: .040"

Replace With:

- Visual Change: LE5-11
- Baffle Modification: Yes

MID RANGE DRIVER (Cont'd)

Exact Acoustic Replacement: No.
Slightly different. Replace both units in a stereo pair.

Additional Parts Currently Available*:

- Dome: Was 54721 (Paper); Now 51868 (Alum.)
- Trim Gasket: 29931

HIGH FREQUENCY DRIVER:

- Diaphragm Kit: 077
- Nom. Impedance: D16R2405
- Dynamic Test Input V: 16 Ohm
- Sweep Frequency Hz: 7
- D.C. Resistance Ohms: 1000-3000
- Gap Gauge: 5.7 minimum
- Notes: 6.7 maximum
- Visual Change: .025"
- Baffle Modification: Test With Network.

Do not crease diaphragm.

If Not Serviceable,

- Replace With: 2405H
- Visual Change: Yes
- Baffle Modification: No
- Exact Acoustic Replacement: Yes
- Additional Parts Currently Available*:
- Mounting Gasket: 51795

SYSTEM SPECIFICATIONS:

NOT AVAILABLE

*Other parts may also be available. Check with JBL for details.