



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER: 135A
 Cone Kit: C8R2235
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 10
 Sweep Frequency Hz: 20-1200
 D.C. Resistance Ohms: 5.7 minimum
 6.9 maximum

Gap Gauge: .057"
 Notes: Aquaplas On Cone.

Drivers with 2 step frame edge require gasket P/N 53880.

If Not Serviceable,
 Replace With: 2235H
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No.

Slightly different. Replace both units in a stereo pair.

Additional Parts Currently Available*:

MID RANGE DRIVER: LE5-3
 Cone Kit: C8RLE59
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 4
 Sweep Frequency Hz: 75-3000
 D.C. Resistance Ohms: 5.6 minimum
 6.6 maximum

Gap Gauge: .040"
 Notes: Dome Inverted

If Not Serviceable,
 Replace With: LE5-10
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No.

Slightly different. Replace both units in a stereo pair.

Additional Parts Currently Available*:

HIGH FREQUENCY DRIVER: LE25
 Diaphragm Kit: D8RLE25
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 3
 Sweep Frequency Hz: 500-1200
 D.C. Resistance Ohms: 3.7 minimum
 4.2 maximum

Gap Gauge: .029"
 Notes: Kit includes parts

for similar models. Use required parts only.

If Not Serviceable,
 Replace With: 035TiA

Visual Change: Yes
 Baffle Modification: Yes
 Exact Acoustic Replacement: No.

Slightly different. replace both units in a stereo pair.

Additional Parts Currently Available*:

Trim Ring: 50402
 Mounting Gasket: 50949-01
 Dome: 21606

SYSTEM SPECIFICATIONS:

Nominal Impedance: 8 Ohm
 Power Capacity: 75 Watts
 Crossover Frequencies: Continuous Program
 1200 Hz, 7500 Hz
 Sensitivity: 80dB (1 Watt @ 15 Feet)
 Enclosure Dim: 27-1/2" x 36-1/2" x 17-1/4" D
 70cm x 93cm x 44cm

Shipping Weight: 131 lbs. - 59 kg.

Additional Parts Currently Available*:

Binding Posts: Red: 10243
 Black: 10244

*Other parts may also be available. Check with JBL for details.