



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	308G-1
Cone Kit:	C4R308G-1
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	5
Sweep Frequency Hz:	30-1200
D.C. Resistance Ohms:	4.8 min/5.8 max
Gap Gauge:	.051"
Notes:	
If Not Serviceable, Replace With:	Currently Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A

Additional Parts Currently Available*:	
Dome:	61521
Trim Ring:	61513-01

HIGH FREQUENCY DRIVER:	LE25-2
Diaphragm Kit:	D8RLE252
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	3
Sweep Frequency Hz:	500-1200
D.C. Resistance Ohms:	3.6 min/4.4 max
Gap Gauge:	.029"

HIGH FREQUENCY DRIVER (Cont'd)

Notes:	Kit includes parts for similar models. Use required parts only.
If Not Serviceable, Replace With:	035TiA
Visual Change:	Yes
Baffle Modification:	Yes
Exact Acoustic Replacement:	No. Use as a last resort. Replace both units in a stereo pair.
Additional Parts Currently Available*:	
Trim Ring:	53363
Mounting Gasket:	50949-01
Dome:	21606

SYSTEM SPECIFICATIONS:

Nom. Impedance:	6 Ohm
Rec. Amp Power Range:	10-60 Watts Continuous Sine Wave Per Channel
Crossover Frequency:	2000 Hz
Sensitivity:	89dB (1 Watt @ 1 Meter)
Enclosure Dim:	21-1/2" x 13-1/2" x 11-3/16" D 546mm x 343mm x 284mm
Shipping Weight:	31 lbs. - 14 kg.
Additional Parts Currently Available*:	
Binding Posts: Red:	56131
Black:	56130

*Other parts may also be available. Check with JBL for details.