

SPECIFICATIONS

DYNAMIC RANGE	90dB
BANDWIDTH, DRY DELAY	10Hz to 20kHz 20Hz to 10kHz
DISTORTION (THD) @ 1kHz	dry, 0dBV, 0.5% max. wet, 0dBV, 1.0% max. dry, +4dBV, 0.65% max. wet, +4dBV, 1.2% max.
DELAY RANGE	0.5 to 1024ms
MODULATION DEPTH	0 (none) to 8:1
SWEEP SPEED	0.1sec to 25sec
INPUT	510k ohm single-ended, ¼" phone jack, handles instrument and single-ended line-level signals.
OUTPUT(S)	Single-ended, ¼" phone jacks, drives 600 ohms.
MAX. INPUT LEVEL	+20dBV (ref. .775VRMS)
MAX. OUTPUT	+20dBm (ref. .775VRMS)
REMOTE SWITCH LOGIC	Grounding terminal engages.
POWER CONSUMPTION	20 watts
POWER	120 VAC, 50/60Hz
DIMENSIONS	L-10.5" x W-19" x H-1.75" (483 x 44 x 269mm)
WEIGHT	6.5lbs (14.33kg); 10lbs (22kg) shipping
OPTION	220 or 240 VAC 50/60Hz
ACCESSORY	FS-2 DUAL FOOTSWITCH (with ¼" STEREO CORD)

